




Code	<b>6655</b>
Typology	recessed ceiling wall,
IP grade	40
Allimentation	24Vdc
Finishes	<b>.01</b> White
Light source	<b>/W</b> 18W 2260lm 24V 4000K CRI>90 <b>/WW</b> 18W 2020lm 24V 3000K CRI>90 <b>/XW</b> 18W 1890lm 24V 2700k CRI>90
Net weight	1,00 kg
	30 cm
	0,00 cm

## ELEMENTI DI SISTEMA

Optional corner profile to facilitate installation in plasterboard	<b>0242/300</b>	0,30 kg
Optional corner profile to facilitate installation in plasterboard	<b>0242/100</b>	0,10 kg
Optional corner profile to facilitate installation in plasterboard	<b>0242/200</b>	0,20 kg



## ACCESSORIES

	<b>0156</b>	0,13 kg
	<b>0157</b>	0,29 kg
Driver 24V - 60W	<b>0160</b>	0,29 kg
	<b>0161/100</b>	0,34 kg
Dimmer 12/24V, PUSH - 1...10V - DALI Constant voltage dimmer 12/24/48V	<b>0110/DIM</b> <b>.DIM</b> DIM	0,10 kg

	<b>0717/DIM60</b>	0,17 kg
	<b>.DIM</b> DIM	
<hr/>		
	<b>0717/DIM100</b>	0,12 kg
	<b>.DIM</b> DIM	
<hr/>		
LED Emergency Unit LED Emergency Unit	<b>0115/EM</b>	0,43 kg
<hr/>		