



|               |   |
|---------------|---|
| Code          | <b>6701</b>   |
| Typology      | recessed ceiling wall,  |
| IP grade      | 20  |
| Allimentation | 24Vdc   |
| Finishes      | <b>.02</b> Black  |
| Light source  | <b>/W</b> 4W 444lm 24V 4000K CRI>90<br><b>/WW</b> 4W 405lm 24V 3000K CRI>90<br><b>/XW</b> 4W 360lm 24V 2700k CRI>90 |
| Net weight    | 0,00 kg   |
|               | 5,90 cm   |

## ACCESSORIES

|   |                                       |         |
|---|---------------------------------------|---------|
|   | <b>0156</b>                           | 0,13 kg |
|   | <b>0157</b>                           | 0,29 kg |
| Driver 24V - 60W  | <b>0160</b>                           | 0,29 kg |
|   | <b>0161/100</b>                       | 0,34 kg |
| Dimmer 12/24V, PUSH - 1...10V - DALI Constant voltage<br>dimmer 12/24/48V | <b>0110/DIM</b><br><b>.DIM</b> DIM    | 0,10 kg |
|   | <b>0717/DIM60</b><br><b>.DIM</b> DIM  | 0,17 kg |
|   | <b>0717/DIM100</b><br><b>.DIM</b> DIM | 0,12 kg |
| LED Emergency Unit LED Emergency Unit                                     | <b>0115/EM</b>                        | 0,43 kg |