1

		>	
			*
1	0		
	_		

	IP40 📣	
RECESSED CEILING WALL		
Code	6320	
Description	Recessed micro spotlight (IP40) direct light with round aluminum body.	
Year of production	2007	
Туроlоду	recessed ceiling wall,	
Material	aluminium	
Light Emission	live	
IP grade	IP40	
Allimentation	350mA - 2,9Vdc	
Finishes	.01 White	
	.32 Satin nickel	

₩ 1W 158lm 4000K /WW 1W 150lm 3000K /XW 1W 143lm 2700k

0,04 lb


7,87 inch

0,79 inch

Light source

Net weight

K



ACCESSORIES

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.

Dot Design ABS Studio

	Slat adapter for DOT	0208	0,01 lb
	Plastic back case	0215	0,00 lb
	Kit: box + perforated plaster	0212	0,00 lb
	led direct current driver 350mA	0128	0,00 lb
A CONTRACT OF			
5 5 45 T			

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.





AND DO	multipower dimmable led driver in contiunous current	0141/DIM .DIM 💿 DIM	0,00 lb
A A	dALI multipower contiunous current dimmable led driver	0141/DALI .DALI 🚥 DALI	0,00 lb
and the second s	multipower dimmable led driver in contiunous current	0145	0,00 lb
200	dALI multipower contiunous current dimmable led driver	0145/DALI .PUSH PUSH .1-10V ⊡ 1-10V .DALI DALI	0,00 lb

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.