




Code	<b>6656</b>
Typology	recessed ceiling wall,
IP grade	40
Allimentation	24Vdc
Finishes	<b>.01</b> White
Light source	<b>/W</b> 27W 24V 4000K <b>/WW</b> 27W 24V 3000K <b>/XW</b> 27W 24V 2700k
Net weight	1,50 kg

## ELEMENTI DI SISTEMA



Optional corner profile to facilitate installation in plasterboard **0242/100** 0,10 kg

Optional corner profile to facilitate installation in plasterboard **0242/300** 0,30 kg

Optional corner profile to facilitate installation in plasterboard **0242/200** 0,20 kg

## ACCESSORIES



**0156** 0,13 kg

**0157** 0,29 kg

Driver 24V - 60W **0160** 0,29 kg

**0161/100** 0,34 kg

Dimmer 12/24V, PUSH - 1...10V - DALI Constant voltage  
dimmer 12/24/48V **0110/DIM** 0,10 kg  
**.DIM** DIM

	<b>0717/DIM60</b>	0,17 kg
	<b>.DIM</b>  DIM	
<hr/>		
	<b>0717/DIM100</b>	0,12 kg
	<b>.DIM</b>  DIM	
<hr/>		
LED Emergency Unit LED Emergency Unit	<b>0115/EM</b>	0,43 kg
<hr/>		