Newton Spots Slim




1

Design officinadiarchitettura&design



F 🔃 😿 🖡	
RECESSED CEILING	
Code	U6470
Description	Recessed projector for plasterboard ceilings, with swivel rod, aluminum body and COB LED direct light.
Year of production	2019
Туроlоду	recessed ceiling
Material	aluminium
Light Emission	live
IP grade	20
Allimentation	500mA - 17,8Vdc
Finishes	.01 White
	.02 Black
Light source	/₩ 8,9W 1353Im 17.8V 4000K CRI>90
	/WW 8,9W 1303Im 17.8V 3000K CRI>90
	/★₩ 8,9W 1244Im 17.8V 2700k CRI>90
Net weight	1,10 lb
	2,01 inch



ACCESSORIES

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.

Newton Spots Slim



Design officinadiarchitettura&design

Glass diffuser - sandblasted Pyrex Frosted Pyrex glass diffuser for NEWTON SLIM	0265 .01 White .02 Black	0,22 lb
led direct current driver 500mA	0127	0,00 lb
led direct current driver 350mA	0128	0,00 lb
 multipower dimmable led driver in contiunous current	0141/DIM .DIM DIM	0,00 lb

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.

Newton Spots Slim



Design officinadiarchitettura&design

AND DO	dALI multipower contiunous current dimmable led driver	0141/DALI .DALI 🚥 DALI	0,00 lb
Contraction of the second seco	multipower dimmable led driver in contiunous current	0145	0,00 lb
202	dALI multipower contiunous current dimmable led driver	0145/DALI .DIM 1-10V-PUSH .1-10V IIIII 1-10V .DALI IIIII DALI	0,00 lb

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.