



Code	6316
Year of production	2023
Typology	recessed ceiling,
Material	aluminium
IP grade	20
Allimentation	350mA - 2,9Vdc
Finishes	.01 White .32 Satin nickel
Light source	/W 1W 158lm 4000K /WW 1W 158lm 3000K /XW 1W 158lm 2700k
Net weight	0,07 kg
	2,00 cm

ACCESSORIES

	Plastic Plastic Box Plastic back case	0215	0,00 kg

	Kit: box + perforated plaster	0212	0,00 kg

	350 mA Driver 1-6 Spot	0125	0,02 kg
 	350 mA Driver 1-10 Spot led direct current driver 350mA	0128	0,00 kg
	Multi-power dimmable driver PUSH - 1....10V, 5-14 Spot multipower dimmable led driver in contiuous current	0141/DIM .DIM DIM	0,00 kg
	Multi -power DALI dimmable driver, 4-14 Spot dALI multipower contiuous current dimmable led driver	0141/DALI .DALI DALI	0,00 kg
	Multi-power dimmable driver PUSH - 1....10V, 1-21 Spot multipower dimmable led driver in contiuous current	0145	0,00 kg
	Multi-power DALI dimmable driver, 1-21 Spot dALI multipower contiuous current dimmable led driver	0145/DALI .DIM 1-10V-PUSH .1-10V 1-10V .DALI DALI	0,00 kg