

IRIS 2 SPOTS SNODI

Design Lux Studio



Codice	6753
Tipologia	incasso plafone parete
Grado IP	20
Allimentazione	350mA - 17Vdc
Finiture	.01 Bianco .02 Nero
Sorgente luminosa	/W 5.9W 885lm 17V 4000K CRI>90 /WW 5.9W 836lm 17V 3000K CRI>90 /XW 5.9W 800lm 17V 2700k CRI>90
Peso netto	0,25 Kg
	5,50 cm

ACCESSORI

Frangiluce - Louvres Frangiluce per Iris	0267/S	0,00 Kg
	.01 Bianco	
	.02 Nero	

Driver 350 mA 1 Spot	0125	0,02 Kg
----------------------	-------------	---------

Multi-power dimmable driver PUSH - 1...10V, 1-2 Spot	0129	0,12 Kg
--	-------------	---------



Multi-power DALI dimmable driver, 1-2 Spot Driver dimmerabile DALI multipotenza in corrente continua IN: 110V-240V OUT :350mA,500mA,700mA 12VDC-10W 24VDC-20W	0129/DALI	0,00 Kg
	.DALI	



Multi-power dimmable driver PUSH - 1....10V, 1-2 Spot led driver dimmerabile multipower in corrente continua

0141/DIM

0,00 Kg

.DIM DIM



Multi -power DALI dimmable driver, 1-2 Spot led driver dimmerabile DALI multipower in corrente continua

0141/DALI

0,00 Kg

.DALI DALI

