

# IRIS 2 SPOTS SNODI

Design Lux Studio



Code	<b>6753</b>
Typology	recessed ceiling wall
IP grade	20
Allimentation	350mA - 17Vdc
Finishes	<b>.01</b> White <b>.02</b> Black
Light source	<b>/W</b> 5.9W 885lm 17V 4000K CRI>90 <b>/WW</b> 5.9W 836lm 17V 3000K CRI>90 <b>/XW</b> 5.9W 800lm 17V 2700k CRI>90
Net weight	0,25 Kg
	5,50 cm

## ACCESSORIES

Frangiluce - Louvres Lightbreak for Iris	<b>0267/S</b>	0,00 Kg
	<b>.01</b> White	
	<b>.02</b> Black	

350 mA Driver 1 Spot	<b>0125</b>	0,02 Kg
----------------------	-------------	---------

Multi-power dimmable driver PUSH - 1...10V, 1-2 Spot	<b>0129</b>	0,12 Kg
--	-------------	---------



Multi-power DALI dimmable driver, 1-2 Spot DALI multipotential direct current dimmable driver IN:110V-240V OUT :350mA,500mA,700mA 12VDC-10W 24VDC-20W	<b>0129/DALI</b> <b>.DALI</b>	0,00 Kg
---	----------------------------------	---------



Multi-power dimmable driver PUSH - 1....10V, 1-2 Spot  
multipower dimmable led driver in continuous current

**0141/DIM**

0,00 Kg

**.DIM** DIM



Multi -power DALI dimmable driver, 1-2 Spot dALI  
multipower continuous current dimmable led driver

**0141/DALI**

0,00 Kg

**.DALI** DALI

