


1



RECESSED CEILING WALL	、 	
Code	6351	
Description	Square recessed spotlight IP40 asymmetrical light dissipator made of anodized aluminum.	
Year of production	2008	
Туроlоду	recessed ceiling wall,	
Material	aluminium	
Light Emission	live	
IP grade	IP40	
Allimentation	500mA - 2,9Vdc	
Finishes	.01 White	
	.45 Anodized aluminum	
Light source	/₩ 1.5W 221Im 4000K	
	/WW 1.5W 210lm 3000K	
	/XW 1.5W 210Im 2700k	
Net weight	0,15 lb	
×	7,87 inch	
	1,50 inch	
~		





ACCESSORIES

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.



	Plastic back case	0217	0,00 lb
.0.	Kit: box + perforated plaster	0214	0,00 lb
$ \begin{array}{c} \underline{2,3^{"}}\\ \underline{0,3^{"}}\\ \underline{0,3^{"}}\\ \underline{0,3^{"}}\\ \underline{1,5^{"}}\\ \underline{2^{"}}\\ \end{array} $			
	led direct current driver 500mA	0127	0,00 lb
1 1 1 3 3 45' 1			
	led direct current driver 350mA	0128	0,00 lb
[8] [9] (1) [8] (45) (7) (7) (7) (7) (7) (7) (7) (7			

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.





A A A A A A A A A A A A A A A A A A A	multipower dimmable led driver in contiunous current	0141/DIM .DIM 💿 DIM	0,00 lb
A A A A A A A A A A A A A A A A A A A	dALI multipower contiunous current dimmable led driver	0141/DALI .DALI 🚥 DALI	0,00 lb
Contraction of the second seco	multipower dimmable led driver in contiunous current	0145	0,00 lb
Carl Carl	dALI multipower contiunous current dimmable led driver	0145/DALI .PUSH PUSH .1-10V IIII 1-10V .DALI IIII DALI	0,00 lb

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milan - tel. +39 02 339586.1 - fax. +39 02 3535112 - info@egoluce.com - www.egoluce.com

This data sheet is the property of EGOLUCE srl. All rights reserved. The photographs, equipment descriptions, quoted drawings and photometric values mentioned are for information only and do not constitute any commitment on the part of our company, which reserves the right to make any changes it deems appropriate at any time and without prior notice.