


ZEPPELIN ADJUSTABLE



Design ABS Studio



Code **6411**

Description IP67 walkable recessed adjustable spotlight with AISI 316L stainless steel round flange, aluminum heat sink, optical apertures of 11°, 25° and 45° and 30 cm neoprene cable.

Year of production 2013

Typology recessed ceiling wall floor,

Material INOX AISI 316L

Light Emission *live*

IP grade 67

Allimentation 500mA - 2,9Vdc

Finishes **.33** Brushed steel

Light source
/W 1.5W 221lm 4000K
/WW 1.5W 210lm 3000K
/XW 1.5W 199lm 2700k



Net weight 0,22 kg



30 cm



6,00 cm



6 cm

ACCESSORIES

ZEPPELIN ADJUSTABLE




Design ABS Studio



Kit draining junction box + IP connector Kit draining junction box + IP connector Kit: Zeppelin Maxi drainage formwork + IP connector

0230


0,00 kg



Wall formwork Wall plastic Box Pear shaped formwork

0232

0,00 kg



Plasterboard mounting accessory Spring for plasterboard Spring for ZEPPELIN ADJUSTABLE

0238

0,04 kg



350 mA Driver 1-6 Spot

0125

0,02 kg

500 mA Driver 1-6 Spot led direct current driver 500mA

0127

0,00 kg



Multi-power dimmable driver PUSH - 1....10V, 2-11 Spot
multipower dimmable led driver in continuous current

0141/DIM
.DIM DIM

0,00 kg



Multi-power DALI dimmable driver, 2-11 Spot dALI
multipower continuous current dimmable led driver

0141/DALI
.DALI DALI

0,00 kg



Multi-power dimmable driver PUSH - 1....10V, 1-21 Spot
multipower dimmable led driver in continuous current

0145

0,00 kg



Multi-power DALI dimmable driver, 1-21 Spot dALI
multipower continuous current dimmable led driver

0145/DALI
.DIM 1-10V-PUSH
.1-10V 1-10V
.DALI DALI

0,00 kg



IP67 350 mA Driver, 1-12 Spot

0031/IP

0,10 kg

IP67 500 mA Driver, 1-7 Spot

0143/IP

0,10 kg